

## WINMAG1213 Installation Instructions

Winchester 1200 & 1300 12ga. / 20ga. Pump Shotguns

**WARNING: UNLOAD AND PROPERLY CLEAR THE WEAPON BEFORE ATTEMPTING TO INSTALL ANY COMPONENT!!!**

1. Unscrew the forend cap and remove the barrel from the receiver.
2. Remove the magazine spring retainer by depressing the spring clip and sliding the retainer from the magazine tube. Note: The magazine spring is under tension. **USE CAUTION WHEN REMOVING THE RETAINER**
3. Remove the factory magazine spring, 3 shot plug and follower from the tube.
4. Thoroughly clean the interior of the magazine tube and **LIGHTLY** coat it with any lubricant.
5. Slide the new magazine follower into the tube with the solid end facing the receiver.
6. Slide the stainless steel magazine spring into the tube, insert the 3 shot plug into the end of the spring and put the retainer over the plug.
7. While pushing the spring into the tube, carefully guide the retainer into the end of the magazine tube. You will have to guide the spring coils into the tube until the retainer contacts it.
8. Push the retainer into the magazine tube until the retainer is flush with the end of the magazine tube.
9. Reassemble the barrel and forend cap.

**You are now ready to enjoy your newly upgraded magazine tube.**

